

Versa Controls Product Catalogue

SmartGage-T7H



Input Channels	Maximum up to 8 Nos. LVDT sensors. (Refer Ordering information for type, make, model of LVDT sensors)
User Interface	7" Touch screen Colour LCD display (Dot Matrix: 800 x 480- RGB)
Units	microns
Resolution	0.1µm/1µm
Display Views	Dial & DRO
Dial Range	+/-30 Micron, +/-80 Micron, +/-150 Micron
Result Display in Run mode	CUR, MIN, MAX, AVG, OVALITY readings with Job counters
Charts	IMR/X-Bar/R Chart
IMR Chart Results	CURRENT,MIN,MAX,AVG,OVALITY
X-Bar Chart Results	CURRENT,MIN,MAX,AVG,OVALITY
R Chart Results	CURRENT,MIN,MAX,AVG,OVALITY
Output Results	Maximum results 6
Functionality	Auto switching of result screen when job placed in fixture
PC Interface	Ethernet (For Fetching Data on Customer demand at Cost)
USB host interface	USB2.0 Compliant for Mass Storage Device up to 4GB & Keyboard/Mouse can be interface
Measurement	OD/ID
Indications	OK,REJECT ,REWORK band in Dial
	Job placed/Job measurement process and Job Removed messages.
Calibration	Double master configurable
Reports Format	Excel (*.csv)
Power Supply	230VAC through 3 pin power cord
Memory	In built micro SD card of 4GB for data storage
Interface	DVI Interface on customer demand at cost